

DATA SHEET

High voltage test device HA 1885J



High voltage test device HA 1885J
Plug-in 19" / 5 HU in housing

Description	High voltage tester with a fully electronic high voltage source up to 500 VA power. This performance and a short circuit current > 200 mA is required by global standards and is met by these devices. The in Europe required standards for work station safety at test stations of more than 1,000 V such as safety control panels and potential-free high voltage are also met. Thereby a global use in the test bay, in production and in the laboratory is possible.	
High voltage test AC	Voltage range	100 up to 5,500 V
	Current range	0 up to 100 mA
	Short circuit current	> 200 mA
High voltage test DC	Voltage range	100 up to 6,000 V
	Current range	0 up to 100 mA
	Residual ripple	< 3 %
Insulation measurement DC	Voltage range	100 up to 6,000 V
	Measuring range (voltage dependent)	250 kΩ up to 1 GΩ
	Residual ripple	< 3 %
ARC detection (optional)	Range	0 up to 100%
Subjective tests	Picture step / text step	subjective or informative
General data	Safety power panel	built-in
	Threshold values	all programmable
	Error message	visual and audible
	Clock / calendar	internal
	Ramp function	programmable (IEC 601)
	Generator	fully electronic, digital technology
	Memory	up to 64 Gbyte
	Additional function	programmable inputs and outputs
	Dimensions (HxWxD) and weight	222 x 483 x 487 mm / ca. 24.0 kg 8.7 x 19.0 x 19.2 in. / ca. 59.9 lbs.
Mains supply	90 up to 250 V, 50 Hz / 60 Hz	
Interfaces	Computer interfaces	USB, RS 232, Ethernet / LAN, CAN
	Digital interface 24 VDC	8 input + 8 output
	Analogue interfaces 10 VDC	2 x input + 1 x output
Operation	Touch	10.1"-TFT colour display